



German standard wall mounting enclosure equipped with bipolar terminal blocks and two interchangeable flanges (1 flange with knock-out elements and 1 flange with quick entry cable glands).

|                           |                    |                         |                                                 |
|---------------------------|--------------------|-------------------------|-------------------------------------------------|
| Insulation class          | II                 | Colour                  | Grey RAL 7035                                   |
| Outer dim. LxHxD (mm)     | 298x260x140        | IP degree               | IP65                                            |
| Installation              | Wall mounting      | Mechanical resistance   | IK07                                            |
| Door colour               | Smoked Transparent | Terminal block N (mm²)  | (3x25)+(10x10)                                  |
| Terminal block T (mm²)    | (3x25)+(10x10)     | No. of modules EN 50022 | 12                                              |
| Glow Wire Test            | 750 °C             | Standard                | IEC EN 60670-1; IEC EN 60670-24; DIN VDE 0603-1 |
| Operating temperature     | -25 +60 °C         | Electrocod              | 0321                                            |
| Thermo-pressure with ball | 70 °C              | Pole 1 (mm²)            | N (3x35) + (10x10)                              |
| Pole 2 (mm²)              | E (3x35) + (10x10) |                         |                                                 |

## DIMENSIONAL

## TECHNICAL SYMBOLOGY



II

IP

IP65

IK

IK07

GWT

750 °C



-25 +60 °C



70 °C

## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 22/06/2021

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice