



Systems of accessories for electrical installations used for residential, tertiary and industrial applications. The system consists of fasteners for pipes and cables, cable fittings, accessories for rigid pipes (RK Series) and flexible conduit (DF Series). The system include also a wide variety of cable ties (52FS Range) and terminal blocks (44 Range).

Colour	Grey RAL 7035	IP degree	IP55
Material	Flexible polymer	For ext. conduits max (mm)	32
Mounting hole Ø (mm)	37	Description	Cable gland for conduits
Glow Wire Test	960 °C	Operating temperature	-5 +60 °C
Electrocod	36A	Standard	EN 61386-1 - EN 60670-1 (as applicable)

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Solvents			Mineral oil	UV rays
	Hexane	Benzol	Acetone		
Resistant	Not resistant	Limited resistance	Resistant	Resistant	Resistant

DIMENSIONAL

TECHNICAL SYMBOLOGY

IP

IP55

GWT

960 °C



-5 +60 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 22/06/2021

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice